



EF 300mm f/2.8L IS II USM Specification Sheet

Optical Features/Specifications

Angle of view (horizontal, vertical, diagonal)	6°50', 4°35', 8°15'
Lens construction (elements/groups)	16/12
No. of diaphragm blades	9
Minimum aperture	32
Closest focussing distance (m)	2.0
Maximum magnification (x)	0.18
Distance Information	Provided
Image stabilizer	4-stops
AF actuator	Ring USM ³

Physical Specifications

Dust/moisture resistance ⁴	Yes
Filter diameter (mm)	52 Drop in
Max. diameter x length (mm)	128 x 248
Weight (g)	2400

Accessories

Lens Cap	E-145C
Lens hood	ET-120(WII)
Lens case/pouch	Lens Case 300B
Maximum number of Hood III compatible with Gelatin Filter Holder III	NC ⁸
Maximum number of Hood IV compatible with Gelatin Filter Holder IV	NC ⁸
Magnification with Extension Tube EF12 II	0.22-0.04
Magnification with Extension Tube EF25 II	0.28-0.09
Extender Compatibility	Compatible
Other Accessories	Canon drop-in 52mm filters

All data is based on Canon standard testing methods except where indicated.

Subject to change without notice.

³ Full time Manual focus

⁴ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

⁸ Use 52mm drop in filter holder