

Printer		SELPHY CP-780
PRINTING SYSTEM		
	Method Maximum Resolution Colours	Dye-sublimation thermal transfer printing system 300 x 300 dpi 3 colour inks with over coating, 256 levels per colour (24 bit colour depth)
MEDIA & CARTRIDGE		
	Postcard Size Wide Size L Size Credit Card Size Credit Card Size Stickers Mini Stickers Ink Cartridge Image Longevity	148 x 100mm - [KP-36IP, KP-72IP/IN, KP-108IP/IN] 100 x 200mm - [KW-24IP] (2) 119 x 89mm - [KL-36IP] (2) 86 x 54mm - [KC-36IP] (2) 86 x 54mm - [KC-18IF] (2) 22.0 x 17.3mm (x8 stickers on one sheet) - [KC-18IL] (2) Included with media 100 Years Print (3)
MEDIA INPUT		
	Sheet Feeder	Auto feed from paper cassette
PRINT SPEEDS		
	Postcard Size Wide Size L Size Credit Card Size Credit Card Size Stickers Mini Stickers	approx. 4.7 sec (4) approx. 60 sec (4) approx. 39 sec (4) approx. 24 sec (4) approx. 24 sec (4) approx. 24 sec (4)
PRINTING		
	Print Modes Print Settings	All Image Print, DPOF Image Print, Fixed Size Layout, ID Photo Print, Movie Print, Single Image Print, 2-up, 4-up and 8-up Layout, Index print (5) Image Optimize, Borderless, Bordered, Date Print, File Name Print, My Colors <5 modes>, Red -Eye Correction (5)
PRINT METHOD		
	Direct Printing From a Camera Direct From a Memory Card Direct From a Camera Phone Print From a Computer	PictBridge compliant Supported card types: Compact Flash, Memory Stick, Memory Stick PRO, Memory Stick PRO Duo, Memory Stick DUO, Microdrive, miniSD, mini SDHC, MMC, MMCplus, HC MMCplus, MMCmobile, SD, SDHC, RS-MMC, microSD(7), microSDHC(7), MMCmicro(7), Memory Stick micro(7), xD-Picture Card (7) Optional Bluetooth Unit BU-30 (printing from some mobile camera phones & PDA's) (8) Yes, requires standard USB cable
INTERFACE		
	Camera Computer TV Viewer LCD Monitor	USB type A port on printer, WiFi IEEE 802.11b (with Digital IXUS WIRELESS and Wireless Print Adapter WA-1E) USB type B port on printer 2.5" Colour TFT viewer with multi-language user interface (10) 2.5" Colour TFT viewer with multi-language user interface (10)
SUPPORTED OPERATING SYSTEM		
	PC Macintosh	Windows XP SP2-3 / Vista (Incl. SP1) Mac OS X v10.4 - v10.5
SOFTWARE		
	Browsing & Printing Drivers	PC/Mac: SELPHY Photo Print PC / Mac
POWER SOURCE		
	AC Power Supply Battery Pack Power Consumption	Yes, supplied Yes, optional (Approx. 36 + Postcard Size prints per full charge) Approx. 4W (standby), approx. 60W (printing)
ACCESSORIES		
	Paper Cassette Power Supply & Battery Chargers Other	Postcard Size paper cassette [PCP-CP300], Wide paper cassette [PCW-CP100], L size paper cassette [PCL-CP300], Card Size [PCC-CP300] CA-CP200W Power adapter, Battery Pack NB-CP2L BU-30 Bluetooth Unit for printing from compatible camera phones and PDA's (8)
PHYSICAL SPECIFICATIONS		
	Operating Environment Dimensions Weight	5 - 40 °C, 20 - 80% humidity 176 x 132.6 x 75.6mm (printer only without protrusions) 940g (Excluding Ink/ Paper Integrated Cartridge)

Subject to change without notice.

(1) Gold/Silver printing available via PC or in selected modes only

(2) Requires optional paper cassette

(3) To test the image permanence of prints that are stored in an album, we use an accelerated testing method as how the image permanence of silver-

(4) Print speed can vary dependent on data size, print method, memory card and capacity and is measured from start of printing excluding paper

(5) Modes/features available may differ dependent on camera model or use of memory card to print

(6) Content is transferred to the internal printer memory via memory card, using SELPHY Contents Utility.

(7) Requires adapter (sold separately)

(8) Mobile phones and PDA's must be Bluetooth enabled and support Bluetooth version 1.1 or above Photo printing only - pictures must be in the JPEG

(9) Pictures must be taken in the JPEG format and transferred using the IrOBEX or IrMc by vNOTE protocol