

Printer	SELPHY CP790	
PRINTING SYSTEM		
	Method	Dye-sublimation thermal transfer printing system
	Maximum Resolution	300 x 300 dpi
	Colours	3 colour inks with over coating, 256 levels per colour (24 bit colour depth)
MEDIA & CARTRIDGE		
	Postcard Size	148 x 100mm - [KP-36IP, KP-72IP/IN, KP-108IP/IN]
	Wide Size	100 x 200mm - [KW-24IP] (2)
	L Size	119 x 89mm - [KL-36IP] (2)
	Credit Card Size	86 x 54mm - [KC-36IP] (2)
	Credit Card Size Stickers	86 x 54mm - [KC-18IF] (2)
	Mini Stickers	22.0 x 17.3mm (x8 stickers on one sheet) - [KC-18IL] (2)
	Ink Cartridge	Included with media
	Image Longevity	100 Years Print (3)
MEDIA INPUT		
	Sheet Feeder	Auto feed from paper cassette
PRINT SPEEDS		
	Postcard Size	approx. 47 sec (4)
	Wide Size	approx. 60 sec (4)
	L Size	approx. 39 sec (4)
	Credit Card Size	approx. 24 sec (4)
	Credit Card Size Stickers	approx. 24 sec (4)
	Mini Stickers	approx. 24 sec (4)
PRINTING		
	Print Modes	All Image Print, Creative Print (Frame, Calendar, Photo Diary), DPOF Image Print, Fixed Size Layout, ID Photo Print, Movie Print, Single Image Print, Trimming Print, 2-up, 4-up and 8-up Layout, Index print (5)
	Print Settings	Image Optimize, Borderless, Bordered, Date Print, File Name Print, My Colors <7 modes>, Red -Eye Correction (5)
PRINT METHOD		
	Direct Printing From a Camera	PictBridge compliant
	Direct From a Memory Card	Supported card types: Compact Flash, Memory Stick, Memory Stick PRO, Memory Stick PRO Duo, Memory Stick DUO, Microdrive, miniSD, mini SDHC, MMC, MMCplus, HC MMCplus Card, MMCmobile, SD, SDHC, RS-MMC, microSD(7), microSDHC(7), MMCmicro(7), Memory Stick micro(7), xD-Picture Card (7)
	Direct From a Camera Phone	Optional Bluetooth Unit BU-30 (printing from some mobile camera phones & PDA's) (8), IrDA IR (printing from some mobile camera phones) (9), IrSimple (printing from some mobile devices) (9)
	Print From a Computer	Yes, requires standard USB cable
INTERFACE		
	Camera	USB type A port on printer, WiFi IEEE 802.11b (with Digital IXUS WIRELESS and Wireless Print Adapter WA-1E)
	Computer	USB type B port on printer
	LCD Monitor	3.0" Colour TFT viewer with multi-language user interface (10)

SUPPORTED OPERATING SYSTEM		
	PC Macintosh	Windows XP SP2-3 / Vista (Incl. SP1) Mac OS X v10.4 - v10.5
SOFTWARE		
	Browsing & Printing Drivers	PC/Mac: SELPHY Photo Print PC / Mac
POWER SOURCE		
	AC Power Supply Battery Pack Power Consumption	Yes, supplied Yes, optional (Approx. 36 + Postcard Size prints per full charge) Approx. 4W (standby), approx. 60W (printing)
ACCESSORIES		
	Paper Cassette Power Supply & Battery Chargers Other	Postcard Size paper cassette [PCP-CP300], Wide paper cassette [PCW-CP100], L size paper cassette [PCL-CP300], Card Size [PCC-CP300] CA-CP200W Power adapter, Battery Pack NB-CP2L BU-30 Bluetooth Unit for printing from compatible camera phones and PDA's (8)
PHYSICAL SPECIFICATIONS		
	Operating Environment Dimensions Weight	5 - 40 °C, 20 - 80% humidity 246.9 x 178.0 x 86.4mm (printer only without protrusions) 1100g (Excluding Ink/ Paper Integrated Cartridge)

All data is based on Canon's standard testing methods.

Subject to change without notice.

(2) Requires optional paper cassette

(3) To test the image permanence of prints that are stored in an album, we use an accelerated testing method as how the image permanence of silver-halide photo papers are measured when stored in dark places. Print samples are printed with the optical density of 1.0 (each Bk, C, M, Y). The samples are kept in a certain environment of high temperature and 50% humidity. The rate of the decrease in the optical density and rate of yellow discoloration are recorded. The recorded results are then converted to the length of time when print image is kept in an environment of 23 / 50% humidity. <Criteria for estimation of print longevity> 'The point where monochromatic/ reflective optical density shows loss of 30% (starting density of 1.0).

(4) Print speed can vary dependent on data size, print method, memory card and capacity and is measured from start of printing excluding paper handling

(5) Modes/features available may differ dependent on camera model or use of memory card to print

(7) Requires adapter (sold separately)

(8) Mobile phones and PDA's must be Bluetooth enabled and support Bluetooth version 1.1 or above Photo printing only - pictures must be in the JPEG format. Bluetooth operation depends on the device and software version used

(9) Pictures must be taken in the JPEG format and transferred using the IrOBEX or IrMc by vNOTE protocol

(10) Supported languages are: English, German, French, Italian, Spanish, Japanese, Simplified Chinese